



Product Sheet EVERCOAT EASY SAND



EVERCOAT EASY SAND


Polyester finishing and blending putty

Skim coat for
pinholes and minor
imperfections


Flowable putty fully compatible for mixing
with EZ Ultralite for complete viscosity
adjustment and control



Contains ZNX-7



Exceptionally easy to
sand



Quick curing



Product Sheet EVERCOAT EASY SAND

Features and Benefits

Excellent adhesion properties



Multi substrate application

Finish coat for filler



Eliminates pinholes

Contains Hattonite



Minimises heat build up and abrasive clogging

Substrates

Zinc coated steel

Polyester Filler

Steel

Galvanized steel

Aluminium

SMC

OE paint & clear coat

Hard plastics

Composite plastics

Applications

Body repair

Multi substrate application

Finishing stopper/putty

Skim coat and spot repair



Product Sheet EVERCOAT EASY SAND

Suited for



Automotive Refinishing



Composite Industries



Industry & Manufacturing

Type

EVERCOAT

EVERCOAT

Technical Specifications

VOC	Max 97 g/l VOC
Colour	White
Package Qty.	6
Shelf Life	18 months
Storage Temperature	25 °C
Capacity	880 ml
Sandability	10-15 minutes
Application Temperature	25 °C
Curing Ratio	2% hardener
Physical State	Liquid
Solubility	Not soluble in cold and warm water
Working Time	5-6 minutes
Maximum Build	3 mm (sanded)