





EVERCOAT POLY-FLEX

Flexible polyester glazing putty

Finishing glaze coat
over body filler for
plastic bumpers and
components



Self levelling



Exceptionally easy to
sand



Excellent filling
properties

Skim coat for pinholes and minor
imperfections



Product Sheet EVERCOAT POLY-FLEX

Features and Benefits

Excellent adhesion properties



Multi substrate application

Flowable viscosity



Ideal for skim coating and spot filling minor imperfections

Extremely flexible



For rigid and semi rigid plastic repairs

Substrates

Polyester Filler

SMC

Hard plastics

Composite plastics

Flexible plastics

Applications

Body repair

Finishing stopper/putty

Flexible plastic repair

Skim coat and spot repair



Product Sheet EVERCOAT POLY-FLEX

Suited for



Automotive Refinishing



Composite Industries



Industry & Manufacturing

Type

EVERCOAT

EVERCOAT

Technical Specifications

Colour	Light Grey
Package Qty.	6
VOC	Max 97 g/l VOC
Storage Temperature	25 °C
Sandability	20-25 minutes
Curing Ratio	2% hardener
Physical State	Liquid
Solubility	Not soluble in cold and warm water
Working Time	5-6 minutes
Maximum Build	3 mm (sanded)
Shelf Life	18 month
Capacity	880 ml
Application Temperature	25 °C